
# Diplomat™

Seating Capacity	5 Adults	
Dimensions	92" x 92" x 35 1/2".	4 10
	(234 cm x 234 cm x 90 cm)	
Corner Radius	16" (41 cm)	Tools A
Dry Weight	900 lbs (408 kg)	0
Filled Weight (Average Fill)	3 650 lbs (1 656 kg)	6
Water Capacity (Average Fill)	330 US gallons (1,250 Liters)	
Shipping Weight		2 0
Export Shipping Weight:	950 lbs (431 kg) D1 SmartHUB™ full color glass touch control	
Electronic Controls		m 388
	panel; access to control jets, temperature,	38* U . ) a
<b>D</b> 4	settings and maintenance schedule	
Pump 1	North America (60 Hz): 2-Speed, 4.0 HP break,	
	2.5 HP continuous, 48 Frame	
Export (50 Hz):	1-Speed, 2.0 HP continuousNorth America (60 Hz): 1-Speed, 3.6 HP break,	
Pump 2	North America (60 Hz): 1-Speed, 3.6 HP break,	
	2.5 HP continuous, 48 Frame	Optional
Export (50 Hz):	1-Speed, 2.0 HP continuous	<del>-</del>
Circulation Pump	Yes	escutcheon jets
Fountain Pump		
Filtration (factory default)	24/7 Filtration (Purge Cycles 2 x 10 minutes)	
Total VCR Jets	45	
	1 Pillow Mini Storm Rotator, 2 Pillow Cluster Shower Directional, 4 Power Storm	
	Dual Rotator, 4 Power Storm Directional, 2 Mini Stor	
	Directional	
Seat 2 Jets		
	1 Pillow Mini Storm Rotator, 2 Pillow Cluster Shower	Directional 2 Power Storm
	Rotator, 4 Power Storm Directional, 2 Mini Storm Dir	
Seat 4 Jets	1 Power Storm Multi Port	
Soat 5 Ultral ounge lete	1 Pillow Mini Storm Rotator, 2 Pillow Cluster Shower Directional, 1 Power Storm	
Footwell (6)	Rotator, 7 Milli Storm Rotator, 2 Milli Storm Directional	
Manage Calcators	i Typhoon	
Massage Selectors		
Special reatures	Tactile Therapy, Spa Status Light, 3 Flex Therapy Pillow, UltraLounge, Aux ControlUltraPure System; Two 75 ft filter cartridge; 8" Weir	
LED Lighting	Liquid FA	
Optional	Exterior Lights  Adobo Top, Stanoridgo Croy, Moyan Proven	
	Adobe Tan, Stoneridge Grey, Mayan Brown	
	Driftwood, Cherry, Summer Pine, Vintage Cedar, Midnight Maple	
Acrylic Colors	Moonstone, UltraLife, Sand, Sunstone, Smoked Marble, Blue Topaz, Gray Marble,	
	Desert Stone	
Headrests	3 Flex Therapy Pillow	
Water Feature	Fountain with independent flow rate (on or off) adjustment; powered by the foun-	
	tain pump	
Heater	2.1, 3.4, 5.5 kW	
Export (50Hz)		
Electrical Requirements:	North America (60 Hz): 240 VAC@30A, 40A or 50A	
	Export (50 Hz): 230 VAC@1x16A, 1x32A, 2x16A, 3x16A or suitably rated	
	circuit breaker to comply with local electrical cod	des. Certain countries may
	require dual power inputs	-
Warranty*	North America (60 Hz): Lifetime for UltraLife Shell Surface, 7 Years Acrylic	
•	Shell Surface, 5 Years Plumbing, 5 Years Equipment and Controls, Lifetime for	
	EnviroTect Cabinet, 7 Years for Terracina Cabinet, 1 Year Water Purification	
	System, 2 Years for Jet Insert, 1 Year for Jet Escutcheon, 2 Years Lights, 1 Year	
	Stereo;	
	Export (50 Hz): 10 Years for UltraLife Shell Surface, 7 Years Acrylic Shell	
	Surface, 5 Years Plumbing, 5 Years Equipment and Controls, 5 Years for	
	EnviroTect Cabinet, 2 Years for Terracina Cabinet, 1 Year Water Purification	
	System, 2 Years for Jet Insert, 1 Year for Jet Esci	
	1 Year Stereo	atonicon, z rears Lights,
Audio System (Ontional)	Fully Integrated Stereo System with Bluetooth capab	nility 4 premium eneakers and
Audio Oystein (Optional)	a subwoofer	omity, a premium speakers and
Wi-Fi (Optional)		
ττι τι (Φρειστιαι)		

<sup>\*(</sup>See Warranty Document for Specific Details)

## **Diplomat**

## **Massage Selector Diagram**



Spa Operation Subject to Change without Notice

## **Seat Depths**


1 = 24.00" (60.96 cm) 2 = 20.00" (50.80 cm) 3 = 29.00" (73.66 cm) 4 = 24.00" (60.96 cm) 5 = 24.00" (60.96 cm) 6 = 31.00" (78.74 cm) Listed dimensions represent distance from top of acrylic to lowest point in seat. Tolerance ± 0.5" (1.27 cm).



DV2 C = Diverter Valve 2 (Neutral Position)

## **Diplomat**

## **Jet Designation**



Dimensions/Operation/Specifications are Subject to Change Without Notice

#### 45 Total Jets



Mini Storm Rotator (9)



Power Storm Multi Port (1)



Mini Storm Directional (10)



Typhoon Jet (1)

#### **Total Jets**



Power Storm Rotator (3)



Power Storm Dual Rotator (4)



Power Storm Directional (8)



Flex Therapy Pillow (3)




(2)





## **Diplomat**



- Note: 1. Subject to change without notice.
  - 2. Engineering specs may differ slightly from brochure.
  - 3. For E-Z lifter installation allow 18" (45.7cm) clearances on the backside of the spa.
  - 4. Alternative cabinets may add significant weight. Ask your dealer for exact details.
  - 5. This is the approximate location for drilling a hole if you must bring the power line in through the bottom of the spa. Be careful not to puncture a plumbing line inside the equipment compartment (drill from the inside compartment out).

Dimensions/Specifications are Subject to Change Without Notice (Tolerance ± 0.5" [1.27 cm]).