

Jacuzzi J-225

Specifications

Seating Capacity	6-7 Adults
Dimensions	80" x 80" x 33" (204 cm x 204 cm x 84 cm); For Complete Dimensions, See page 76
Dry Weight	619 lbs (281 kg)
Filled Weight (Average Fill)	3,571 lbs (1,620 kg)
Water Capacity (Average Fill) ...	354 US gallons (1,341 Liters)
Electronic Controls	Solid state electronic controls with LED readout, programmable temperature, filtration, and heat cycles
Pump 1	North America (60 Hz): 2-Speed, 2.5 HP brake, 1.5 HP continuous, 48 Frame
Export (50 Hz):	2-Speed, 2.0 HP continuous
Circulation Pump	No
Total Jets	26
Seat A Jets	3 SL3 Directional, 1 SL5R Rotational
Seat B Jets	1 SLR Rotational, 1 SL3 Directional, 8 SL Directional
Seat C Jet	1 SL3R Rotational
Seat D Jets	6 SL3 Directional
Seat E Jets	4 SL3R Rotational
Massage Selectors	None
Air Controls	2
Water Management System	One 50 ft ² filter cartridge on jets pump 1, ClearRay Active Oxygen® System
Export (50 Hz):	ClearRay Active Oxygen® System
LED Lighting	LED Lighting System (Interior Surround); Standard Exterior Light
Cabinet Colors	Horizon Gray, Pecan
Acrylic Colors	Platinum, Silver Pearl, Morning Mist, Midnight, Canyon, Monaco (while quantities last)
Headrests	4
Heater:	North America (60 Hz): 120V 1kW or 240V 4.0 kW, High Flow
Export (50 Hz):	High Flow, 2.7 kW
Electrical Requirements:	North America (60 Hz): 120V@15A (GFCI cord) 240 VAC@30A or 40A Export (50 Hz): 220-240 VAC@1x16A, 1x32A or 2 out of 3-phase (see manual) or suitably rated circuit breaker to comply with local electrical codes. Certain countries may require dual power inputs; two GFCI RCD breakers are required for this configuration.
Warranty*	North America (60 Hz): 5 Years Shell, 3 Years Shell Surface, 3 Years Plumbing Component Leaks, 3 Years Equipment and Controls; 1 Year Cabinet, 1 Year Jets Export (50 Hz): 5 Years Shell, 3 Years Shell Surface, 3 Years Plumbing Component Leaks, 3 Years Equipment and Controls, 1 Year Cabinet, 1 Year Jets
Special Features (Optional)	SmartTub® Module
Audio System (Optional)	N/A



*(See Warranty Document for Specific Details)

Dimensions/Specifications are Subject to Change Without Notice

Jacuzzi J-225

Operation/Seat Depths



Jets are always on when the Jets Pump 1 is running.

Air Control 1:
Opens/Closes
Air Inlet to Jet
Group A

Air Control 2:
Opens/Closes
Air Inlet to Jet
Group B

26 Total Jets



Spa Operation Subject to Change without Notice

Seat Depths

A = 23.50" (59.69 cm)
B = 21.00" (53.34 cm)
C = 27.25" (69.22 cm)
D = 21.88" (55.56 cm)
E = 23.88" (60.64 cm)

F = 21.50" (54.61 cm)
G = 26.00" (66.04 cm)
H = 17.50" (44.45 cm)
I = 28.00" (71.12 cm)


Listed dimensions represent distance from top of acrylic to lowest point in seat. Tolerance $\pm 0.5"$ (1.27 cm).



Dimensions/Specifications are Subject to Change Without Notice

Jacuzzi J-225


Dimensions



IMPORTANT! Always measure each hot tub for exact dimensions BEFORE designing its foundational support and/or decking.



Cabinet Radius:
 ≈ 9.0" (22.86 cm)



Dimensions/specifications subject to change without notice. Tolerance: ± 0.5" (1.27 cm)
 Dimensions/specifications subject to change without notice. Tolerance ±0.5" (1.27 cm)